

554,975

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 November 2004 (11.11.2004)

PCT

(10) International Publication Number
WO 2004/097889 A2

(51) International Patent Classification⁷: **H01J 35/00**

(21) International Application Number: **PCT/GB2004/001741**

(22) International Filing Date: 23 April 2004 (23.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0309383.8 25 April 2003 (25.04.2003) GB

(71) Applicant (for all designated States except US): CXR LIMITED [GB/GB]; Unit 5, Riverside Business Centre, Walnut Tree Close, Guildford GU1 4UG (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MORTON, Edward, James [GB/GB]; 37 Banders Rise, Guildford, Surrey GU1 2SL (GB). LUGGAR, Russell, David


(74) Agent: BARKER BRETTTELL; 138 Hagley Road, Edgbaston, Birmingham B16 9PW (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, ZW).

[Continued on next page]

(54) Title: X-RAY TUBE ELECTRON SOURCES



WO 2004/097889 A2

(57) Abstract: An X-ray tube includes an emitter wire (18) enclosed in a suppressor (14, 16). An extraction grid comprises a number of parallel wires (22) extending perpendicular to the emitter wire, and a focusing grid comprises a number of wires (20) parallel to the grid wires (20) and spaced apart at equal spacing to the grid wires (20). The grid wires are connected by means of switches to a positive extracting potential or a negative inhibiting potential, and the switches are controlled so that at any one time a pair of adjacent grid wires (22) are connected together to form an extracting pair, which produce an electron beam. The position of the beam is moved by switching different pairs of grid wires to the extracting potential.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*